



*Drive to the Future,
Charge for the Change*



DC Fast CCS-2 EV Charger



Auto
Cut-off



WiFi
Enabled



IP54
Certified



Bluetooth
Enabled



IOT
Enabled



RFID
Enabled



Parameter	Characteristic	DC Charger CCS2				
Model	EV Charger DC CCS2					
Power	Rated Power	15 kW	30 kW	60 kW	120 kW	240 kW
	Number of outputs	Single Gun	Single or Dual Gun	Single or Dual Gun	Single or Dual Gun	Dual Gun
	Output current (per gun)	40A max	80A max	150A max	200A Max	200A Max
	Input voltage	415 Vac (±10%), 50 Hz Three phase				
	Output Charging Outlet	CCS2				
	Output voltage	150-1000V DC				
	Power Factor	≥0.98				
	Efficiency	≥95				
User Interface	Display	7" TFT LCD with touch				
	Push Button	Emergency Stop				
	User Authorization	RFID + OCPP v1.6				
Environment	Ambient Temperature	-20°C to 55°C				
	Storage Temperature	-40°C to 70°C				
	Altitude	<2000 m				
	Humidity	<95%, Non condensing				
Communication	External	WiFi, RS485, LAN/4G + OCPPv1.6				
	Metering and Billing	Available				
	Charging Operation	RFID Card/ Scan QR Code/Mobile App				
Protection	Input/Output protection	Over/Under voltage protection, Overload protection, Short circuit protection, Current leakage protection, Grounding protection, Surge protection, Over/Under temperature Protection				
	Protection level	IP54				
	Cooling	Forced Air Cooling				
Miscellaneous	As per	IEC 61851-1:2017, IEC 61851 21-2				
	Safety	CE				
	Certification	ARAI				
	Mounting	Wall/ Stand Mount	Wall/ Floor Mount	Floor Mount	Floor Mount	Floor Mount

Charging Station Management Software



Open charge point protocol 1.6

Dynamic
Pricing Capability

Easy to Access
& Statistics

Daily Report
Generation

Detail Charger
Management Dashboard

Real Time Charger
Management

Error & Complain
Management system

Driven by data
analysis & AI



C/402 Ganesh Glory-11 Nr. BSNL Office, Godrej Garden City Road,
Sarkhej - Gandhinagar Hwy, Jagatpur, Ahmedabad, Gujarat 382481

+91 70168 08092 | info@tectonicpower.com | www.tectonicpower.com

Support by

#startupindia

